



W292S4498 Hillside Rd. Waukesha, WI 53189

262-896-6780 Fax 262-896-6756

[www.midwestindustriesinc.com](http://www.midwestindustriesinc.com)

## **NGAL Fixed Front Sight Installation Instructions**

### **MI-NGAL-FS**

Please read all instructions step-by-step before proceeding to install the sight.

(If instructions are not followed, your warranty is void. If you are not comfortable with this install please have the sight installed by a qualified gunsmith.)

**Before proceeding, make sure your rifle is pointed in a safe direction, magazine removed and chamber empty. Remove all ammunition and magazines from the workspace.**

- 1.) Locate the forward most T-slot on the top of your hand guard rail.
- 2.) Remove any existing front sights, lasers, lights or accessories that will block the front sight.
- 3.) Loosen allen head screw on MI-NGAL-FS sight and be careful to not lose screw or clamp.
- 4.) Clip the MI-NGAL-FS into the forward most slot on the top rail with the engraved MI facing forward.
- 5.) Slide the MI-NGAL-FS forward in the slot and torque the clamp screw to 20 inch/pounds.
- 6.) When installing NGAL Laser open filters to allow it to slide up to the rear of the fixed front sight.
- 7.) Reinstall any accessories onto hand guard.
- 8.) Perform a function check to make sure the firearm is in good working condition and all parts were reinstalled correctly.

**Includes front sight tool. Adjustments one click: Rifle 1.5 MOA / Carbine 2 MOA adjustments**

**Turning sight post clockwise will raise your point of impact, counterclockwise will lower it.**

**Modification or alteration to this part (to include custom coatings) voids all factory warranties.**

If you have any questions about the install please give us a call at:

**262-896-6780**